



液压胶辊压套机

TOP ROLLER SLIPPING MACHINE

YT430 液压胶辊压套机

YT430 TOP ROLLER SLIPPING MACHINE



技术参数

1. 压套胶辊最大长度	430mm
2. 最高工作压力	14MPa
3. 最大前进速度	0.96M/min
4. 返回速度	1.5M/min

Technical Parameters:

1. Maximum length of pressing cots:	430mm
2. Highest working pressure:	14MPa
3. Maximum advancing speed:	0.96M/min
4. Return speed:	1.5M/min

YT430液压胶辊压套机是我公司最新设计研制的胶辊压套和拆卸专用设备,它吸收了国内外各种压套机的优点,并采用进口液压元件组装而成,所以体积小、结构紧凑、操作方便、压力强劲。适用各种规格的胶辊拆装之用。

Top roller slipping machine model YT430 is our newly-developed special device for rubber cots pressing & dismantling. It is covered the advantages of domestic & imported top roller slipping machines. It is assembled by imported hydraulic components, little volume, compact structure, easy-operated, strong pressure compose its feature. It is suitable for fixing & dismantling different rubber cots.

YT430Q 液压胶辊压套机

YT430Q TOP ROLLER SLIPPING MACHINE

YT430Q液压胶辊压套机是我公司在YT430基础上新设计研制的胶辊压套和拆卸专用设备,是一种多用途的新型胶辊压拆机械,其中采用了变频调速技术,调节压胶辊时的快慢,并在原来的结构上增加了短胶辊压拆装置,达到一机两用。并采用进口液压元件组装而成。所以体积小、结构紧凑、操作方便、压力强劲。适用各种规格的胶辊拆装之用。

Model YT430Q Top roller slipping machine is Our newly-developed special device for rubber cots pressing & dismantling base on YT430, it multipurpose and adept frequently conversion technology to control speed, also could apply to short cots pressing & dismantling. It is assembled by imported hydraulic components, little volume, compact structure, easy-operated, strong pressure compose its feature. It is suitable for fixing & dismantling different rubber cots.



技术参数

1. 工作电压	AC200V
2. 功率	750W
3. 压套胶辊最大长度	430mm
4. 最高工作压力	14Mpa
5. 最大前进速度	0.96M/m
6. 返回速度	1.5M/m

Technical parameters

1. working pressure:	AC200V
2. power:	750W
3. Maximum length of pressing cot:	430mm
4. Highest working pressure:	14Mpa
5. Maximum advancing speed:	0.96M/m
6. return speed:	1.5M/m